



**BUILT-IN
CIRCUIT
BREAKER**



LED
**ENERGY
-EFFICIENT
AND
MAINTENANCE
-FREE**

OLIMP 24 LED OLIMP 230 LED



- two versions of power supply
- horizontal and vertical mounting
- classic design

OLIMP lamp is a safety element in gate automation. Energy-saving LED light source used in the lamp, ensures long-term, maintenance-free operation. Two versions of power supply 24V and 230V, built-breaker, horizontal and vertical mounting, allow to use OLIMP lamp in any kind of automation.



OLIMP 24 LED OLIMP 230 LED

flashing lamp

▶ OLIMP 24 LED / OLIMP 230 LED parameters

power supply: 24V AC/DC / 230VAC
power: max 5W
operating temperature: -20°C / +55°C
lampshade: orange, PMMA
technology: LED
vitality: <50 000h
usage: signal light
mounting: horizontal and vertical
ingress protection: IP-44
operating mode: constant or impulse 0,5s
shock and vibration resistance: high
weight: 170g
antenna: (only OLIMP 230 LED) built-in dual-band antenna

▶ Lamp dimensions



Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl

