

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control




focus focus-flash



- guaranteed range 15m
- high resistance to interference from other light sources
- splash-proof case
- NO or NC output contacts

Main usage is to work in gate automation systems as safety barrier.



➤ Basic parameters

external housing dimensions (WxDxH): 62x28x100mm
 mounting: surface-mounted, splash-proof housing, IP-54
 housing: ABS, polycarbonate covers
 operating temperature (min./max.): -20°C / +55°C
 weight: 165g

➤ Photocell parameters

guaranteed operating range: 1-15m
 transmitter and receiver power supply: 24VAC/DC ±10%
 receiver power consumption: max. 25mA
 transmitter power consumption: max. 25mA

➤ Signal lamp parameters (FLASH version)

lamp power supply: 24VAC/DC ±10%
 lamp current consumption: 2x40mA
 power: 2x3W
 technology: LED
 vitality: <50 000h
 resistance to shock and vibration: high

➤ Executive elements

output (type / maximum load): NO or NC / 1A (24VAC/DC)

➤ Functionality

user interface: two LED diodes

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control

