

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



NEW!

GALACTIC

Save Time & Money

- programming remotes in the office
- self-activation by the user
- 65 000 installations with a unique code

GALACTIC



- programming remotes outside the installation
- ergonomic, robust remotes with 2 or 4 buttons
- low battery signalling
- 868MHz frequency with complimentary IRS variable rolling code

NEO 2's quality and innovative technical solutions create dimension of comfort and safety. Remote has two or four buttons that can control radio receivers, gate controllers and other DTM devices. Equipped with Galactic function which allows programming and configuring the remote outside the installation.

neo2
GALACTIC



➤ **General parameters**

number of buttons: 2 or 4
frequency: 868MHz
battery: CR2016
max range: 250m
effective radiated power: to 10mW
variable rolling code: 104-bit IRS
number of combinations: 2,02824096E+31
case: plastic
operating temperature (min/max): -10°C / +55°C
weight: 20g
part of: DTM868MHz


➤ **Principle of operation**

1



configuration and settings
in GSOFT programme,
programming the remote
with GALACTIC function
anywhere, eg. in the office

2



provide the remote to user

3



user in receiver radio range initiates adding
a transmitter to receiver by using remote buttons,
since that moment remote is active in the system

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl