

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



slim II



- sync function transmitter - receiver
- redundant relay output
- splash-proof case
- NO or NC output contacts
- high resistance to interference from other light sources

Main usage is to work in gate automation systems as safety barrier.



**SLIM
CASE
35mm**

slim II

safety photocells

➤ General parameters

range: 7m / 15m
view angle adjustment: 200° horizontal
transmitter and receiver supply: 12...24VAC/DC ±10%
receiver current consumption: max 25mA
transmitter current consumption: max 25mA
operating temperature: -20°C / +55°C
case external dimensions: 35x30x110mm
IP protection: IP-54
case material: ABS with polycarbonate front

➤ Executive elements

output (type / maximum load): NO or NC / 1A 24VAC or DC

➤ Functionality

user interface: LEDs signaling power supply and facilitate transmitter and receiver synchronization
additional protection: safety output (in case of damage output turns in violation mode)
two pairs of photocells interference protection: yes, sync function (AC power required)

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl

