## automation systems

HID868 transmitter



Radio

Remotes

Gate Controllers Gate Automation Accessories

Motors

Control



NEW!

## complamentary IRS variable rolling code

- **868MHz** frequency
- FSK modulation
- customized security solutions against radio intrusion
- intelligent adaptation to radio conditions of transmitter and receiver





COMPONENT OF DTM868MHz

**HID 868** 

- easy to use
- additional button to verify radio range

**BE LOST** 

- 4 NO inputs
- low battery signalling

4-channel transmitter HID868 is a component of DTM868MHz series. The use of modern and innovative technologies made it possible to obtain more reliable radio coverage. It is designed for mounting inside installation box with any momentary button. It is characterized by small size and very simple operation. HID868 allows to control home and gate automation devices discretely.





## HID 868

four channel transmitter for built-in

Seneral parameters

inputs (type / number): NO/4

frequency: 868MHz battery: CR2032

maximum range: 250m

effective radiated power: to 10mW variable rolling code: 104-bit IRS

the number of combinations: 2,02824096E+31 operating temperature (min. / max.):  $-20^{\circ}\text{C}/+55^{\circ}\text{C}$ 

IP: 20

mounting: inside installation box


dimensions: 44x37x22mm

weight: 25g

component of: DTM868MHz

Usage example.....





any NO button





HID868 transmitter placed under the button





Radio Receivers

Remotes

Gate Controllers Gate Automation Accessories

Gate Motors Access Control



