## automation systems

miniUVR868 1-channel radio receiver



Radio Receivers

Remote

Gate Controllers Gate
Automation
Accessories

Motors

Control





- programming remotes in the office
- unique authentication code
- programmed remote works immediately in accordance with entered settings
- dedicatedGSOFT application





- programming remotes outside the installation
- advanced and simple programming
- compatible with DTM868MHz series remotes

MiniUVR868 is a compact, onechannel radio receiver designed to work with 230VAC supplied devices. It provides a simple and inexpensive way to expand the functionality of the home and gate automation with remote control. Small housing allows to mount receiver in installation box.







## miniUVR868

1-channel radio receiver

Basic parameters

power supply: 230VAC ±10%

power consumption: 1W

memory: 200 remotes

operating temperature (min./max.): -20°C/+55°C external dimensions (width x depth x height): 44x37x22mm

mounting: installation box weight: 42g

Executive elements

relay output

(type / maximum load): NO or NC/3A/230VAC

output mode: monostable, bistable or momentary

rmonostable mode

hold time: 0,5s/from1s to 127s every1s/from1min.to 127 min. every1 min.

manual control input: NO type

Radio parameters

radio module: integrated, superheterodyne

transmission safety: 104-bit IRS modulation / frequency: FSK/868MHz

antenna: wire

Functionality.

user interface: based on two buttons and five LEDs remote configuration: ability to assign any button to receiver

ability to register remotes

without access to receiver button: easy remote registering function

ability to register remotes

programmed outside the installation: Galactic function

ability to delete single remote: yes, remote presence required

verifying number of registered remotes: yes

Radio
Receivers
Remotes
Remotes
Remotes
Gate
Controllers
Automation
Accessories
Motors
Control
Control

