

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



**MOUNTING
IN INSTALLATION
BOX**

**POWER
SUPPLY
230V**

miniUVR

- remote and manual control
- advanced and simple programming
- maximum output load 3A/230VAC
- compatible with DTM433MHz series remotes

MiniUVR is a compact, one-channel radio receiver designed to work with 230VAC supplied devices. It provides a simple and inexpensive way to expand the functionality of the home and gate automation with remote control. Small housing allows to mount receiver in installation box.

available versions:





miniUVR

1-channel radio receiver

➤ Basic parameters

power supply: 230VAC $\pm 10\%$
power consumption: 1W
memory: 35 remotes
operating temperature (min./max.): $-20^{\circ}\text{C}/+55^{\circ}\text{C}$
external dimensions (width x depth x height): 44x37x22mm
mounting: installation box
weight: 42g

➤ Executive elements

relay output
(type / maximum load): NO or NC/3A/230VAC
output mode: monostable, bistable or momentary
monostable mode
hold time: 0,5s; from 1s to 127s every 1s, and from 1min to 127min every 1min
manual control input: NO type

➤ Radio parameters

radio module: integrated, superheterodyne
transmission safety: 64-bit Keeloq®
modulation / frequency: OOK/433,92MHz
antenna impedance: 50Ω
antenna: wire

➤ Functionality

user interface: based on two buttons and five LEDs
remote configuration: ability to assign any button to receiver
ability to register remotes
without access to receiver button: easy remote registering function
ability to delete single remote: yes, remote presence required
verifying number of registered remotes: yes

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl

