automation systems

signal lamp

POMENA 24 / POMENA 230 / POMENA 24 B / POMENA 230 B



www.dtm.pl

Radio Remotes Gate Au Receivers Controllers Ac

Gate Automation Accessories

Gate Motors Control





- two versions of power supply
- horizontal and vertical mounting
- built-in dual band antenna

The POMENA lamp is a safety element in gate automation. The energy-saving LED light source used in the lamp guarantees many years of maintenance-free operation. Two versions of 24V and 230V power supply, built-in circuit breaker, the possibility of horizontal or vertical mounting, as well as the ability to choose the color version of the housing allow the use of the POMENA lamp in any type of automation.





signal lamp

POMENA parameters

power supply: 24V AC/DC / 230VAC

power: max 5W operating temperature: -20°C / +55°C

lampshade: PMMA, orange or transparent

technology: LED vitality: <50,000h usage: signaling lighting mounting: on the horizontal plane

or vertical with an angle bracket

ingress protection: IP-44

operating mode: continuous or pulse 0.5s

shock and vibration resistance: high

110x118x94mm (without angle bracket)

weight: 180g

antenna: built-in, dual range: 433MHz, 868MHz

Accessories

EXTERNAL ANTENNA ON THE BASIS

frequency: 433MHz or 868MHz dimensions: 115x152x210 mm

cable length: 3m

assembly method: on the lamp base or in the angle bracket

antenna characteristics: omnidirectional



Radio Receivers

Remotes

Gate Controllers Gate Automation Accessories

Gate Motors Access Control





