

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



**ELEMENT
OF
DTM433MHz**



**MEMORY
200
REMOTES**

**TWO
CHANNELS**

mini

available versions:



- service lock
- small dimensions
- power supply 12...24V AC/DC

Mini is a two-channel radio receiver in a small housing. It is characterized by very simple operation while maintaining high functionality. It is designed to work with gate controllers, roller shutters and other automation devices.

mini

2-channel radio receiver

➤ Basic parameters

power supply: 12...24VAC/DC
max power consumption: 55mA (with relays switched on)
memory capacity: 200 remotes from the DTM433MHz series, and in the MULTI version additionally almost all variable-code models working in the KeeLoq® system
operating temperature (min./max): -20°C / +55°C
housing external dimensions: 46 (68 with mounting brackets) x 46 x 22mm
mounting: in an installation box instal60 or larger or inside other devices, IP-20
weight: 42g

➤ Executive elements

relay outputs
(type/number/maximum load): 1xNO/NC + 1xNO/1A (24VAC/DC)
output modes: monostable, bistable or temporary
output hold time adjustment
in monostable mode: 0.5s, from 1 to 127s with a resolution of 1s, and from 1min to 127min with a resolution of 1min

➤ Radio parameters

radio module: integrated, superheterodyne, ensuring high reliability, repeatability and resistance to radio interference
transmission protection: 64-bit KeeLoq®
modulation / frequency: OOK / 433,92Mhz
input impedance of the antenna: 50Ω
antenna: factory wire antenna

➤ Functionality

user interface: hardware interface on six LEDs and two buttons supporting a simple menu
remote configuration: the ability to assign any of the two receiver channels to any button
deleting single remote: the need to have a remote control removed
adding remote without access
to receiver buttons: remote adding function with the option of blocking or unlocking the function
service lock: the ability to disable the remote controls registered to the receiver
number of remotes in memory verification: function of showing the number of remotes entered

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl

