



**230V
POWER
SUPPLY**

**50 000h
VITALITY**

LIBRA230



- resistance to shock and vibration
- built-in interrupter
- low power consumption
- perfectly visible in all weather conditions

LED light bulb LIBRA230 is a replacement for standard Edison's light bulb used in flashing signal lights. LED technology offers high uniformity, long life, low EMI noise and high shock and vibration resistance. It also has the advantage of low power consumption and low heat output, factors that significantly improve reliability. Built-in interrupter allows to cooperate with 230VAC drivers providing continuous power to the lighting lamp.



LIBRA230





Led indicator bulb

General parameters

supply: 230VAC $\pm 10\%$
 wattage: 5,7W
 vitality: 50 000h
 thermal protection: 130°C
 operating temperatures: -25°C / +55°C
 type of thread: E14
 light colour: yellow
 destination: signal lighting
 mode: constant / pulse 0,5s
 shock resistant: yes
 weight: 17g



The bulb work configuration



LED light bulb LIBRA230 usage

Radio
Receivers

Remotes

Gate
Controllers

Gate
Automation
Accessories

Gate
Motors

Access
Control



automation systems

DTM System, ul. Brzeska 7, 87-145 Bydgoszcz, POLAND, tel./fax +48 52 340 15 83, e-mail: dtm@dtm.pl
www.dtm.pl

